



# Skytouch Express Global, Inc

**250 OKANAGAN AVE  
EAST, PENTICTON V2A  
3J7 | 250-493-2245**

**100-1755 SPRINGFIELD  
RD, KELOWNA, BC V1Y  
5V5 | 250-762-9961**

## Water Resistant Laminate Flooring Technical Specification Data

### Skytouch Express Global Inc.

Use	Residential & Commercial
Waterproof Performance	Waxed Edge comes with Aqua Seal Technology, 72h Water Resistance
Size	60" (L) x 9.4" (W) x 12mm(T) / 1515mm (L) x 238mm (W) x 12mm(T)
Material	100% wood fiber, Degradable & Recyclable
Thickness	12mm
Wear Layer	AC4
Embossing:	Embossed in Register (EIR Finish)
Bevel type:	Painted bevel edge
Locking System	Unilin Angle & Drop Lock
Installation	Locking system
Planks/Carton	6 PCS
Sq. Ft./Carton	23.29 SQ. FT
Cartons Per Pallet	44 CTNS
Weight Per Carton	23.80 KGS

### ASTM TEST RESULTS

TESTING	TEST RESULT	REQUIREMENTS
Critical radiant flux	1.06 W/cm2	ASTM E648
Formaldehyde Emission	Not Detected	ASTM D6007-14
Dimensional stability and Curling	Meets or exceeds	ASTM F2199-18
Large Ball Impact Resistance	NOT CRACK	NALFA LF 01-2011
Small Ball Impact Resistance	NOT CRACK	NALFA LF 01-2011
Locking Strength	Meets or exceeds	ISO 24334:2014
Scratch Resistance	No visible scratch	ISO 1518-1:2019
Slip Resistance	PASS	NALFA LF 01-2011, ASTM D2394-2017
Thickness Swell	8~10%	NALFA LF 01-2019
Floorscore	Floorscore Certified	VOC EMISSION TESTING
CARB 2	CARB ATCM Phase 2 Compliant	ASTM D6007-14
EPA TSCA TITLE VI	EPA TSCA Title VI Compliant	ASTM D6007-14